

TRUGLU^{XD}

MOISTURE-CURED PREMIUM
URETHANE ADHESIVE

- ✓ HIGH-STRENGTH, ELASTOMERIC BOND
- ✓ PERMANENT, WATERPROOF BOND
- ✓ FAST GRAB, NON-SLUMP FORMULA
- ✓ EASY INSTALLATION
- ✓ LOW VOC, LOW ODOUR

HEAVY COMMERCIAL
LIGHT COMMERCIAL
MULTI-FAMILY
RESIDENTIAL

 RH 75%	 pH 5-9	 MVER 5lbs	 OPEN TIME 10 min	 WORKING TIME 45-60 mins	 CURE TIME 24 hours
---	--	---	--	---	--



 LIGHT TRAFFIC 4 hours

 HEAVY TRAFFIC 12 hours

TOOL MEASUREMENTS : WIDTH x DEPTH x SPACING

1/8" x 1/8" x 1/8"
Sq Notch
60-70 sf/gal




RESILIENT: Rubber (rolls, sheets, mats)
WOOD: Cork (flooring, underlayment), Hardwood (parquet)

1/16" x 1/16" x 1/16"
Sq Notch
150-180 sf/gal



RESILIENT: Rubber (rolls, sheets, mats)
WOOD: Cork (underlayment)

3/16" x 1/4" x 5/16"
V Notch
up to 50 sf/gal



WOOD: Acrylic Impregnated Plank, Bamboo (not strand woven), Cork (flooring, cork-backed hard surface, underlayment), Hardwood (engineered, parquet, solid)