

LOC Series



Lock Down High Quality in Minutes With LOC Series Interlocking Tiles

**SEAMLESS
INTERLOCK**

**VIRTUALLY
ODOURLESS**

**COMMERCIAL
GRADE**

RECOMMENDED APPLICATIONS

- *Community Centres*
- *Home Gyms*
- *Fitness & Exercise Spaces*
- *Weight Rooms*
- *Play Spaces*
- *Utility Rooms*

FEATURES & BENEFITS

- *High Colour Speckle Content*
- *Quick & Easy Loose Lay Installation for Temporary or Permanent Use*
- *Precision Cut for a Virtually Seamless Finish*
- *Easy to Clean & Maintain*

DISTRIBUTED BY:

LOC Series

PERFECT RUBBER FLOORING
www.perfectrubberflooring.ca



REGARDED AS THE PREMIERE CHOICE FOR PROFESSIONALS AND DIY ALIKE, LOC SERIES INTERLOCKING TILES TRANSFORM ANY SPACE QUICKLY AND EASILY

STANDARD TILE SPECIFICATIONS

SIZE THICKNESS BINDER
2'0" x 2'0" 5/16" (8MM) URETHANE

* CUSTOM THICKNESSES AVAILABLE



COLOURED EPDM GRANULATE

1MM TO 3MM


* THE COLOUR CONCENTRATION OF THE STANDARD TILE IS 30%

GATORLOC SPECIFICATIONS

TEST TYPE	ASTM	RESULTS
SHORE HARDNESS	D-2240	65 +/- 5
DENSITY	D-792	60-80 LBS./CU.FT.
ELONGATION (AT BREAK)	D-412	95%*-120%*
TENSILE STRENGTH	D-412	260-340 PSI
COMPRESSION SET	D-395	-4.8%
VOC EMISSIONS	D-5116	<0.5MG/M ²
RESISTANCE TO CHEMICALS	F-925-02	NO CHANGE
STATIC LOAD LIMIT	F-970	PASSES, 150 PSI
DIE-C TEAR	D-624	80 MIN
SURFACES FLAMMABILITY	D-2859	PASS
COEFFICIENT OF FRICTION	D-1894-95	>0.8*

* VARIES BASED ON COLOUR


NOTE: PHYSICAL PROPERTIES CAN VARY BY PRODUCT TYPE.
INFORMATION ABOVE APPLIES TO THIS PRODUCT ONLY.



0201 Cobalt Frost



0202 Sandstone



0203 Steel Frost



0204 Sable Black

* Additional colours available for custom orders