

# PRO Series



## Are You Ready? PRO Series Rolled Rubber & Interlocking Tiles Have You Covered

**HIGH  
PERFORMANCE**

**MAXIMUM  
DURABILITY**

**COMMERCIAL  
GRADE**

### RECOMMENDED APPLICATIONS

- *Fitness & Exercise Facilities*
- *Schools*
- *Recreation Centres*
- *Community Centres*
- *K9 Facilities*
- *Ice Arenas*
- *Home Gyms*

### FEATURES & BENEFITS

- *High Impact Design for Comfort*
- *Slip Resistant for Added Safety*
- *A Variety of Colours and Thicknesses to Suit any Space*
- *Easy to Clean & Maintain*
- *Economical Option for a Variety of Spaces, Large and Small*

**DISTRIBUTED BY:**



# PRO Series

**PERFECT RUBBER FLOORING**  
www.perfectrubberflooring.ca



WIDELY REGARDED AS THE PREMIER "GREEN"  
RESILIENT FLOORING CHOICE, PRO SERIES ROLLS  
CONTAIN UP TO 92% RECYCLED CONTENT  
AND HAVE LOW VOC EMISSIONS



## QUICK SHIP

	2'x2' Interlock Tiles	4'x25' Rubber Rolls	SPECIAL ORDER 4'x25' Rubber Rolls
Pitch Black	1/4" 3/8"	1/4" 5/16" 3/8" 1/2" 1/8"	
Fog White	1/4" 3/8"	1/4" 5/16" 3/8" 1/2"	
Arctic Blue	1/4" 3/8"	5/16"	1/4" 3/8" 1/2"
Sandstorm		5/16"	1/4" 3/8" 1/2"
Brick Red		5/16"	1/4" 3/8" 1/2"

## PRO SERIES SPECIFICATIONS

SHORE HARDNESS	D-2240	65 +/- 5
DENSITY	D-792	60-80 LBS./CU.FT.
ELONGATION (AT BREAK)	D-412	95%*-120%*
TENSILE STRENGTH	D-412	260-340 PSI
COMPRESSION SET	D-395	-4.8%
VOC EMISSIONS	D-5116	<0.5MG/M <sup>2</sup>
RESISTANCE TO CHEMICALS	F-925-02	NO CHANGE
STATIC LOAD LIMIT	F-970	PASSES, 150 PSI
DIE-C TEAR	D-624	80 MIN
SURFACES FLAMMABILITY	D-2859	PASS
COEFFICIENT OF FRICTION	D-1894-95	>0.8*

\* VARIES BASED ON COLOUR



\* Additional colours  
available for  
custom orders